

CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

Issued to: AOK LED Light Company Limited
East Suite (2/F, Plant 4, St George's Science and
Technology Industrial Park)
3/F, Building 1, St George's Science and Technology
Industrial Park
North Side of Xinyu Road, Xinqiao Street Shenzhen ,
Guangdong,
China 518125

**This is to certify that
representative samples of** IFAM7 - Light-emitting-diode Surface-mounted Luminaires
Certified for Canada
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: CSA C22.2 NO. 250.0-08, 3rd Ed., Issue Date: 2008-09-01,
Revision Date: 2012-10-17

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up
Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's
Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AOK-50WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	LED Surface Mounted Luminaire
AOK-25WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	LED Surface Mounted Luminaire
AOK-240WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-200WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-150WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-100WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-60WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	
AOK-100WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-420WoT-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-300WoT-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-145WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-300WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN"	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

<p>can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.</p>	
<p>AOK-230WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.</p>	LED Surface Mounted Luminaire
<p>AOK-120WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means</p>	LED Surface Mounted Luminaire
<p>AOK-75WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means</p>	LED Surface Mounted Luminaire
<p>AOK-115WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	LED Surface Mounted Luminaire
<p>AOK-115WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where</p>	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

<p>"XX" can be any letters.</p> <p>AOK-145WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>
<p>AOK-180WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>
<p>AOK-180WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>
<p>AOK-200WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>
<p>AOK-300WoT-FV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be 00 for no sensor provided. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by "-KV". May</p>	<p>LED Surface Mounted Luminaire</p>



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	
AOK-300WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-FV-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be 00 for no sensor provided. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by “-KV”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-NVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-75WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-CA-L364473-31-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

<p>PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	
<p>AOK-75WoT-NVS-XX-XX-XXXX-BN-P, where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

Issued to: AOK LED Light Company Limited
East Suite (2/F, Plant 4, St George's Science and
Technology Industrial Park)
3/F, Building 1, St George's Science and Technology
Industrial Park
North Side of Xinyu Road, Xinqiao Street Shenzhen ,
Guangdong,
China 518125

**This is to certify that
representative samples of** IFAM - Light-emitting-diode Surface-mounted Luminaires
See Addendum Page for Product Designation(s).

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 1598, 3rd Ed., Issue Date: 2008-09-17, Revision Date:
2012-10-17

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance does not provide authorization to apply the UL Mark. Only the UL Follow-Up
Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's
Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
AOK-145WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-300WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-230WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-120WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	LED Surface Mounted Luminaire
AOK-75WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

"XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	
AOK-50WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	LED Surface Mounted Luminaire
AOK-25WiP-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C or D for mounting means	LED Surface Mounted Luminaire
AOK-240WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-200WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-150WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-100WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-300WoT-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L"	LED Surface Mounted Luminaire

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	
AOK-60WoH-NV2-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A or B for mounting means	LED Surface Mounted Luminaire
AOK-420WoT-NV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-100WoT-NVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED, second "XX" can be SN or PH or 00 for sensor provided or not, last "XXXX" can be any digits for color temperature, "BN" can be any letter or digits for beam angles, "P" can be A, B, C, D or E for mounting means, may be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7", may be followed by "-R" or "-L" for lens orientation, may be followed by "-XX", which can be any letters for fixture color.	LED Surface Mounted Luminaire
AOK-115WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.	LED Surface Mounted Luminaire
AOK-115WoT-NVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

<p style="text-align: center;">"XX" can be any letters.</p> <p>AOK-145WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	LED Surface Mounted Luminaire
<p>AOK-180WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	LED Surface Mounted Luminaire
<p>AOK-180WoT-NVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	LED Surface Mounted Luminaire
<p>AOK-200WoT-HVS-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	LED Surface Mounted Luminaire
<p>AOK-300WoT-FV-XX-XX-XXXX-BN-P, , where first "XX" can be any letter for manufacturer of LED. Second "XX" can be 00 for no sensor provided. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by "-KV". May</p>	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	
AOK-300WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-FV-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be 00 for no sensor provided. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by “-KV”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-420WoT-NVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-PH277”, “-PH347”, “-KV”, “-PR3” or “-PR7”. May be followed by “-R” or “-L”. May be followed by “-XX”, where “XX” can be any letters.	LED Surface Mounted Luminaire
AOK-75WoT-HVS-XX-XX-XXXX-BN-P, ,where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: “-PH120”, “-	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number UL-US-L364473-11-01218102-1
Report Reference E364473-20181210
Date 27-Jul-2020

<p>PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	
<p>AOK-75WoT-NVS-XX-XX-XXXX-BN-P, where first "XX" can be any letter for manufacturer of LED. Second "XX" can be SN or PH or 00 for sensor provided or not. Last "XXXX" can be any digits for color temperature. "BN" can be any letter or digits for beam angles. "P" can be "A", "B", "C", "D" or "E" for mounting means. May be followed by one or more of following: "-PH120", "-PH277", "-PH347", "-KV", "-PR3" or "-PR7". May be followed by "-R" or "-L". May be followed by "-XX", where "XX" can be any letters.</p>	<p>LED Surface Mounted Luminaire</p>



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

