

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant: LED PANEL LIGHTING CO., LTD

Manufacturer: LED PANEL LIGHTING CO., LTD

Address: 1-6F, No.233 QingFeng Rd, Sanzhong, Qingxi, Dongguan, Guangdong 523000


Address: 1-6F, No.233 QingFeng Rd, Sanzhong, Qingxi, Dongguan, Guangdong 523000

Country: China

Country: China

Party Authorized To Apply Mark: Same as Manufacturer
Report Issuing Office: Intertek Testing Services Hong Kong Limited

Control Number: 5010960


Authorized by: 
for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	Luminaires [UL 1598:2021 Ed.5+R:18Jun2021]
	Luminaires [CSA C22.2#250.0:2021 Ed.5+U1]
Product:	Fixed luminaires
Brand Name:	

Models:

DIPL- followed by 1X1-15TD-, 1X1-24TD-, 1X2-24TD-, 1X4-26TD-, 1X4-32TD-, 2X2-20TD-, R24-26TD-, 2X2-32TD-, 2X2-30D-, 2X2-40D-, 1X4-30D-, 1X4-40D-, 2X4-36D-, 2X4-40D-, 2X4-45D-, 1X2-24D- or 1X1-15D-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

BLIT- followed by 2X2-30D-, 2X2-40D-, 1X4-30D-, 2X4-60D-, 2X4-40D-, 2X4-30D-, 2X4-45DR-, 2X4-40DR-, 2X4-35DR-, 2X4-30DR-, 1X4-35DR-, 1X4-30DR-, 1X4-25DR-, 2X2-40DR-, 2X2-35DR-, 2X2-30DR-, 2X2-25DR-, 2X2-20DR-, 2X4-55D-, 2X4-50D- or 1X4-20DR-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.WOR- followed by DIPL3030-15-, DIPL3030-24-, DIPL3060-24-, DIPL30120-26-, DIPL30120-32-, DIPL6060-20-, DIPL6060-26-, DIPL6060-32-, DIPL6060-30-, DIPL6060-40-, DIPL30120-30-, DIPL30120-40-, DIPL60120-36-, DIPL60120-40-, DIPL60120-45-, BLIT6060-30-, BLIT6060-40-, BLIT30120-30-, BLIT60120-60-, BLIT60120-40- or BLIT60120-30-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.WOR- followed by BLIT60120-45R-, BLIT60120-40R-, BLIT60120-35R-, BLIT60120-30R-, BLIT30120-35R-, BLIT30120-30R-, BLIT30120-25R-, BLIT6060-40R-, BLIT6060-35R-, BLIT6060-30R-, BLIT6060-25R-, BLIT6060-20R-, BLIT60120-55-, BLIT60120-50-, DIPL3060-24-, DIPL3030-15- or BLIT30120-20R-; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters; followed by -RS.BT.CC- followed by 2X4-55WD-, 2X4-40WD-, 1X4-30WD- or 2X2-30WD-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

BT.ECA- followed by 2X4-NND-, 1X4-NND- or 2X2-NND-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.BT.EDC- followed by 2X4-NND-, 1X4-NND- or 2X2-NND-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.BT-2X4-50DR-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

BT.TW3S- followed by 2X4-NND- or 2X2-NND-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

BT.TW5S- followed by 2X4-NND-, 1X4-NND- or 2X2-NND-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

TRF.TWS- followed by 2X4-NND-, 1X4-NND- or 2X2-NND-; followed by two characters; followed by -; followed by two numbers; followed by -; followed by four characters; followed by -RS.

ET-22- followed by 20, 25, 30 or 40; followed by WD-; followed by three characters; followed by -; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters.

ET-24- followed by 30, 35, 40 or 50; followed by WD-; followed by three characters; followed by -; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters.

ET-14- followed by 20, 25 or 30; followed by WD-; followed by three characters; followed by -; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters.

ET-15120-30WD- followed by three characters; followed by -; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters.

STL- followed by 2X2 or 2X4; followed by -40TD-; followed by two characters; followed by -; followed by two characters; followed by -; followed by four characters. **TRF.CA-** followed by **2X2-30D or 2X4-50D**; followed by two characters; followed by -; followed by one character; followed by -; followed by two characters; may be followed by -; may be followed by two characters; may be followed by -; may be followed by one character.

TRD.TR- followed by **2X2- or 2X4-**; followed by one character; followed by -; followed by one character; followed by K; followed by -; followed by one character.