

# Certificate of Compliance

## Certificate Number(s):

UL-US-L364473-11-  
03709102-17

## Report Reference:

E364473-20190730

## Issue Date:

2025-11-26

Issued to:

**AOK LED Light Company Limited**  
**East Suite, 3/F, Building 1, St George's Science, & Technology**  
**Industrial Park. (2/F, Plant 4, St George's Science, & Technology**  
**Industrial Park). North Xinyu Rd, Xinqiao St., Shenzhen,**  
**Guangdong, 518125, CN**

This certificate confirms that representative samples of:

**IFAM - Light-emitting-diode Surface-mounted Luminaires**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 1598, Edition 5, Issue Date 2021-03-26, Revision Date 2024-01-31**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number(s):** UL-US-L364473-11-03709102-17  
**Report reference:** E364473-20190730  
**Issue Date:** 2025-11-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## LED Surface Mounted Luminaire

**Model(s):** SMX-720WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-420WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-580WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-460WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-580WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-460WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-315WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-380WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-720WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-230WiNM-NV-XX-XX-XXXX-XX-XX-XX

**Model(s):** AOK-720WiNM-HV-XX-XX-XXXX-BN-P, AOK-230WiNM-HV-XX-XX-XXXX-BN-P, AOK-315WiNM-HV-XX-XX-XXXX-BN-P, AOK-460WiNM-HV-XX-XX-XXXX-BN-P, AOK-580WiNM-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A.

**Model(s):** AOK-580WiNS-NV-XX-XX-XXXX-BN-P, AOK-460WiNS-NV-XX-XX-XXXX-BN-P, AOK-460WiNS-HV-XX-XX-XXXX-BN-P, AOK-580WiNS-HV-XX-XX-XXXX-BN-P, AOK-720WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B or B1, "D" for mounting bracket D, or "N" for mounting bracket N.

**Model(s):** AOK-720WiNS-NV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B or B1, "D" for mounting bracket D or "N" for mounting bracket N.

**Model(s):** AOK-315WiNS-HV-XX-XX-XXXX-BN-P, AOK-380WiNS-NV-XX-XX-XXXX-BN-P, AOK-315WiNS-NV-XX-XX-XXXX-BN-P, AOK-800WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B, "D" for mounting bracket D, or "N" for mounting bracket N.

**Model(s):** AOK-800WiNS-NV-XX-XX-XXXX-BN-P, AOK-960WiNS-NV-XX-XX-XXXX-BN-P, AOK-960WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B, "D" for mounting bracket D or "N" for mounting bracket N.

**Model(s):** SMX-420WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-380WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-315WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-230WiNM-HV-XX-XX-XXXX-XX-XX-XX, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "XX" which can be any letters or blank to represent Fixture Color, followed by "XX" which can be any letters

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

**Certificate number(s):** UL-US-L364473-11-03709102-17  
**Report reference:** E364473-20190730  
**Issue Date:** 2025-11-26

or blank to represent Accessories.

**Model(s):** AOK-460WiNS-DV-X5-XX-XXXX-15-P, AOK-580WiNS-DV-X5-XX-XXXX-15-P, AOK-720WiNS-DV-X5-XX-XXXX-15-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "B" for mounting bracket B.

**Model(s):** AOK-460WiNS-DV-X3-XX-XXXX-BN-P, AOK-720WiNS-DV-X3-XX-XXXX-BN-P, AOK-580WiNS-DV-X3-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C or "B" for mounting bracket B.

**Model(s):** AOK-315WiNS-DV-X3-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C.

**Model(s):** AOK-380WiNS-DV-X5-XX-XXXX-15-P, AOK-96WiV-HV-XX-XX-XXXX-BN-P, AOK-96WiV-NV-XX-XX-XXXX-BN-P, AOK-315WiNS-DV-X5-XX-XXXX-15-P, AOK-145WiV-NV-XX-XX-XXXX-BN-P, AOK-145WiV-HV-XX-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A..

**Model(s):** AOK-580WiNS-DV-X5-XX-XXXX-XX-P, AOK-720WiNS-DV-X5-XX-XXXX-XX-P, AOK-460WiNS-DV-X5-XX-XXXX-XX-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C or "B" for mounting bracket B.

**Model(s):** AOK-315WiNS-DV-X5-XX-XXXX-XX-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C.

**Model(s):** AOK-960WiNS-DV-X5-XX-XXXX-30-P, AOK-960WiNS-DV-X5-XX-XXXX-15-P , where the first "XX" can be "00", followed by "XXXX" which can be any numbers for temperature colors and color rendering index, "P" can be "A" or "C" for mounting bracket type.

**Model(s):** AOK-460WiNM-NV-XX-XX-XXXX-BN-P, AOK-230WiNM-NV-XX-XX-XXXX-BN-P, AOK-580WiNM-NV-XX-XX-XXXX-BN-P, AOK-720WiNM-NV-XX-XX-XXXX-BN-P, AOK-315WiNM-NV-XX-XX-XXXX-BN-P, AOK-380WiNM-NV-XX-XX-XXXX-BN-P ,where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A

# Certificate of Compliance

## Certificate Number(s):

UL-CA-L364473-31-  
03709102-17

## Report Reference:

E364473-20190730

## Issue Date:

2025-11-26

Issued to:

**AOK LED Light Company Limited**  
**East Suite, 3/F, Building 1, St George's Science, & Technology**  
**Industrial Park. (2/F, Plant 4, St George's Science, &**  
**Technology Industrial Park). North Xinyu Rd, Xinqiao St.,**  
**Shenzhen, Guangdong, 518125, CN**

This certificate confirms that representative samples of:

**IFAM7 - Light-emitting-diode Surface-mounted Luminaires**  
**Certified for Canada**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**CSA C22.2 No. 250.0:21, Edition 5, Issue Date 2021-03-26,**  
**Revision Date 2024-01-31**

**CSA C22.2 NO. 250.0:21, 5th Ed., Issue Date: 2021-03-26,**  
**Revision Date: 2021-06-18**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Manager



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-L364473-31-03709102-17  
Report reference: E364473-20190730  
Issue Date: 2025-11-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

## LED Surface Mounted Luminaire

**Model(s):** SMX-720WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-420WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-580WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-460WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-580WiNM-NV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-460WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-315WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-380WiNM-NV-XX-XX-XXXX-XX-XX-XX, SMX-720WiNM-HV-XX-XX-XXXX-XX-XX-XXXXXX, SMX-230WiNM-NV-XX-XX-XXXX-XX-XX-XX

**Model(s):** AOK-720WiNM-HV-XX-XX-XXXX-BN-P, AOK-230WiNM-HV-XX-XX-XXXX-BN-P, AOK-315WiNM-HV-XX-XX-XXXX-BN-P, AOK-460WiNM-HV-XX-XX-XXXX-BN-P, AOK-580WiNM-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A..

**Model(s):** AOK-580WiNS-NV-XX-XX-XXXX-BN-P, AOK-460WiNS-NV-XX-XX-XXXX-BN-P, AOK-460WiNS-HV-XX-XX-XXXX-BN-P, AOK-580WiNS-HV-XX-XX-XXXX-BN-P, AOK-720WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B or B1, "D" for mounting bracket D, or "N" for mounting bracket N.

**Model(s):** AOK-720WiNS-NV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B or B1, "D" for mounting bracket D or "N" for mounting bracket N.

**Model(s):** AOK-315WiNS-HV-XX-XX-XXXX-BN-P, AOK-380WiNS-NV-XX-XX-XXXX-BN-P, AOK-315WiNS-NV-XX-XX-XXXX-BN-P, AOK-800WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B, "D" for mounting bracket D, or "N" for mounting bracket N.

**Model(s):** AOK-800WiNS-NV-XX-XX-XXXX-BN-P, AOK-960WiNS-NV-XX-XX-XXXX-BN-P, AOK-960WiNS-HV-XX-XX-XXXX-BN-P, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "B" for mounting bracket B, "D" for mounting bracket D or "N" for mounting bracket N.

**Model(s):** SMX-420WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-380WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-315WiNM-HV-XX-XX-XXXX-XX-XX-XX, SMX-230WiNM-HV-XX-XX-XXXX-XX-XX-XX, where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.



# CERTIFICATE OF COMPLIANCE

Certificate number(s): UL-CA-L364473-31-03709102-17  
Report reference: E364473-20190730  
Issue Date: 2025-11-26

*temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "XX" which can be any letters or blank to represent Fixture Color, followed by "XX" which can be any letters or blank to represent Accessories.*

**Model(s):** AOK-460WiNS-DV-X5-XX-XXXX-15-P, AOK-580WiNS-DV-X5-XX-XXXX-15-P, AOK-720WiNS-DV-X5-XX-XXXX-15-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "B" for mounting bracket B.

**Model(s):** AOK-460WiNS-DV-X3-XX-XXXX-BN-P, AOK-720WiNS-DV-X3-XX-XXXX-BN-P, AOK-580WiNS-DV-X3-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C or "B" for mounting bracket B.

**Model(s):** AOK-315WiNS-DV-X3-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C.

**Model(s):** AOK-380WiNS-DV-X5-XX-XXXX-15-P, AOK-96WiV-HV-XX-XX-XXXX-BN-P, AOK-96WiV-NV-XX-XX-XXXX-BN-P, AOK-315WiNS-DV-X5-XX-XXXX-15-P, AOK-145WiV-NV-XX-XX-XXXX-BN-P, AOK-145WiV-HV-XX-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A..

**Model(s):** AOK-580WiNS-DV-X5-XX-XXXX-XX-P, AOK-720WiNS-DV-X5-XX-XXXX-XX-P, AOK-460WiNS-DV-X5-XX-XXXX-XX-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C or "B" for mounting bracket B.

**Model(s):** AOK-315WiNS-DV-X5-XX-XXXX-XX-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for without sensor, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "XX" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A or "C" for mounting bracket C.

**Model(s):** AOK-960WiNS-DV-X5-XX-XXXX-30-P, AOK-960WiNS-DV-X5-XX-XXXX-15-P , where the first "XX" can be "00", followed by "XXXX" which can be any numbers for temperature colors and color rendering index, "P" can be "A" or "C" for mounting bracket type.

**Model(s):** AOK-460WiNM-NV-XX-XX-XXXX-BN-P, AOK-230WiNM-NV-XX-XX-XXXX-BN-P, AOK-580WiNM-NV-XX-XX-XXXX-BN-P, AOK-720WiNM-NV-XX-XX-XXXX-BN-P, AOK-315WiNM-NV-XX-XX-XXXX-BN-P, AOK-380WiNM-NV-XX-XX-XXXX-BN-P , where the first "XX" Can be any letter and digit to represent different brands and size of LED, followed by "XX" which can be "00" for no sensor provided, "SN" for Sensor provided or "PH" for photocontrol provided, followed by "XXXX" which can be any numbers for temperature colors and color rendering index, followed by "BN" which can be any letters or digits for beam angles, followed by "P" which can be "A" for mounting bracket A