

# Certificate of Compliance

**Certificate Number:**

UL-US-2439137-0

**Report Reference:**

E505979-20241010

**Issue Date:**

2024-10-21

Issued to:

**RZ Lighting Co Ltd**  
**4F, Bldg. B, Zhongjing Sci-Tech Park**  
**606 Fengtang Blvd, Bao'an Shenzhen, Guangdong 518103**  
**China**

This certificate confirms that representative samples of:  
**IFAM - Light-emitting-diode Surface-mounted Luminaires**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**UL 1598, Edition 5, Issue Date 2021-03-26, Revision Date 2024-01-31**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



A handwritten signature in black ink, appearing to read 'David Piecuch'.

David Piecuch  
UL Mark Certification Program Owner

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**      UL-US-2439137-0  
**Report reference**        E505979-20241010  
**Date**                        2024-10-21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

<b>Model</b>	<b>Product Description</b>
<p>WP09A-10-40, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser.</p> <p>XX for commercial, can be any two characters or blank.</p>	<p>LED Surface Mounted Luminaire</p>
<p>WP09A-10-80, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser.</p> <p>XX for commercial, can be any two characters or blank.</p>	<p>LED Surface Mounted Luminaire</p>
<p>WP09A-14-120, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser.</p>	<p>LED Surface Mounted Luminaire</p>



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-US-2439137-0  
**Report reference**     E505979-20241010  
**Date**                     2024-10-21

XX for commercial, can be any two characters or blank.	
WP09A-14-40, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire
WP09A-14-80, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire
WP09A-18-150, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire
WP28-10-40, Followed by suffix X-ABCD-XX. X represents voltage, can be L for 120-277V or M for 120-	LED Surface Mounted Luminaire



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-US-2439137-0  
**Report reference**     E505979-20241010  
**Date**                     2024-10-21

<p style="text-align: center;">347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.</p> <p>D can be C3, indicating that CCT is adjustable.</p> <p>XX for commercial, can be any two characters or blank.</p>	
<p>WP28-10-80, Followed by suffix X-ABCD-XX.</p> <p>X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.</p> <p>D can be C3, indicating that CCT is adjustable.</p> <p>XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP28-14-120, Followed by suffix X-ABCD-XX.</p> <p>X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.</p> <p>D can be C3, indicating that CCT is adjustable.</p> <p>XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP28-14-60, Followed by suffix X-ABCD-XX.</p> <p>X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.</p> <p>D can be C3, indicating that CCT is adjustable.</p> <p>XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number** UL-US-2439137-0  
**Report reference** E505979-20241010  
**Date** 2024-10-21

<p>WP28-14-80, Followed by suffix X-ABCD-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. XX for commercial, can be any two characters or blank.</p>	<p>LED Surface Mounted Luminaire</p>
---	--------------------------------------



# Certificate of Compliance

**Certificate Number:**

UL-CA-2429832-0

**Report Reference:**

E505979-20241010

**Issue Date:**

2024-10-21

Issued to:

**RZ Lighting Co Ltd  
4F, Bldg. B, Zhongjing Sci-Tech Park  
606 Fengtang Blvd, Bao'an Shenzhen, Guangdong 518103  
China**

This certificate confirms that representative samples of:  
**IFAM7 - Light-emitting-diode Surface-mounted Luminaires  
Certified for Canada**

**See Addendum Page for Product Designation(s).**

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.

**CSA C22.2 No. 250.0:21, Edition 5, Issue Date 2021-03-26,  
Revision Date 2024-01-31**

Additional Information:

See UL Product iQ® at <https://iq.ulprospector.com> for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



David Piecuch  
UL Mark Certification Program Owner



# CERTIFICATE OF COMPLIANCE

**Certificate number**      UL-CA-2429832-0  
**Report reference**        E505979-20241010  
**Date**                        2024-10-21

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

<b>Model</b>	<b>Product Description</b>
<p>WP09A-10-40, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser.</p> <p>XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP09A-10-80, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser.</p> <p>XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP09A-14-120, Followed by suffix X-ABCD-F-XX.                      X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                      D can be C3, indicating that CCT is adjustable.</p> <p>F represents diffuser, can be PC for polymeric diffuser, or</p>	LED Surface Mounted Luminaire



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**    UL-CA-2429832-0  
**Report reference**     E505979-20241010  
**Date**                     2024-10-21

blank for glass diffuser. XX for commercial, can be any two characters or blank.	
WP09A-14-40, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire
WP09A-14-80, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire
WP09A-18-150, Followed by suffix X-ABCD-F-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. F represents diffuser, can be PC for polymeric diffuser, or blank for glass diffuser. XX for commercial, can be any two characters or blank.	LED Surface Mounted Luminaire



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number**      UL-CA-2429832-0  
**Report reference**        E505979-20241010  
**Date**                        2024-10-21

<p>WP28-10-40, Followed by suffix X-ABCD-XX.                  X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                  D can be C3, indicating that CCT is adjustable.                  XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP28-10-80, Followed by suffix X-ABCD-XX.                  X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                  D can be C3, indicating that CCT is adjustable.                  XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP28-14-120, Followed by suffix X-ABCD-XX.                  X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.                  D can be C3, indicating that CCT is adjustable.                  XX for commercial, can be any two characters or blank.</p>	LED Surface Mounted Luminaire
<p>WP28-14-60, Followed by suffix X-ABCD-XX.                  X represents voltage, can be L for 120-277V or M for 120-347V</p> <p>A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided.</p> <p>B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire.</p> <p>C can be 4, indicating that 4 power is adjustable.</p>	LED Surface Mounted Luminaire



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.

# CERTIFICATE OF COMPLIANCE

**Certificate number** UL-CA-2429832-0  
**Report reference** E505979-20241010  
**Date** 2024-10-21

<p>D can be C3, indicating that CCT is adjustable. XX for commercial, can be any two characters or blank.</p>	
<p>WP28-14-80, Followed by suffix X-ABCD-XX. X represents voltage, can be L for 120-277V or M for 120-347V A represents function, can be S2 for photosensor, S for microwave sensor, S1 for infrared sensor, or blank for not provided. B indicates the dimming type, optionally A or D, A=1-10V/0-10V, D=1-10V/0-10V power adjustment function and dimming wire. C can be 4, indicating that 4 power is adjustable. D can be C3, indicating that CCT is adjustable. XX for commercial, can be any two characters or blank.</p>	<p>LED Surface Mounted Luminaire</p>



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at <https://www.ul.com/contact-us>.