

CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-US-2222067-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

Issued to: RZ Lighting Co Ltd
No. 301 Building10, High-tech Industrial Park
No.156 Fuyuan 1st Road, Fuhai Street, Bao'an District,
Shenzhen, Guangdong 518103
China

This is to certify that representative samples of IFAM - Light-emitting-diode Surface-mounted Luminaires
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the Standard(s) indicated on this Certificate.


Standard(s) for Safety: UL 1598, 5th Ed., Issue Date: 2021-03-26, Revision Date: 2021-06-18

Additional Information: See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-US-2222067-0^JJ
Report Reference L^LE505979-20220521^JJ
Date 14-Jun-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
WP09-100L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-120L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-30L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-40L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-60L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP.	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-US-2222067-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

<p>YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	
<p>WP09-80L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-100L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-120L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-30L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-40L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K.</p>	LED Surface Mounted Luminaire

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-US-2222067-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	
WP09F-60L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09F-80L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-CA-2221602-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

Issued to: RZ Lighting Co Ltd
No. 301 Building10, High-tech Industrial Park
No.156 Fuyuan 1st Road, Fuhai Street, Bao'an District,
Shenzhen, Guangdong 518103
China

This is to certify that representative samples of IFAM7 - Light-emitting-diode Surface-mounted Luminaires
Certified for Canada
See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the
Standard(s) indicated on this Certificate.


Standard(s) for Safety: CSA C22.2 NO. 250.0:21, 5th Ed., Issue Date: 2021-03-26,
Revision Date: 2021-06-18

Additional Information: See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>




CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-CA-2221602-0^JJ
Report Reference L^LE505979-20220521^JJ
Date 14-Jun-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
WP09-100L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-120L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-30L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-40L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09-60L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP.	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-CA-2221602-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

<p>YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	
<p>WP09-80L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-100L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-120L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-30L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.</p>	LED Surface Mounted Luminaire
<p>WP09F-40L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K.</p>	LED Surface Mounted Luminaire

B. Mahrenholz

Bruce Mahrenholz, Director North American Certification Program

UL LLC


Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number L^LUL-CA-2221602-0^J
Report Reference L^LE505979-20220521^J
Date 14-Jun-2022

3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	
WP09F-60L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire
WP09F-80L, Followed by suffix -X-YY-PC or -X-3CCT-PC. X denote control type, can be D, S, M, P, SM, SP, C, CS, CM, CP, CSM, CSP. YY denote color temperature, can be 27-65, e.g. 30=3000k, 40=4000k, 50=5000K, 57=5700K, 65=6500K. 3CCT denote Any color temperature (CCT) of LED. PC denote Diffuser type, can be PC for polymeric Diffuser, or blank for glass Diffuser.	LED Surface Mounted Luminaire



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

